

PCB Inspection Conveyor

Feature:

1. PLC Program control.
2. Easy way of belt replacement.
3. Heavy bottom design to prevent shifting.
4. PCB Precise stopping in position.
5. Anti stuck track design.
6. Inspect/ Auto Mode.
7. SMEMA compatible.

Option: Conveyor can be customize according to requirement.

such as Length, no of PCB stoppage, adding ESD Dust cover, etc...



SMA-2A100L

Technique Parameter

Description	Used for visual inspection station
Conveyor Type	Flat Belt
Conveyor Speed	0.5-20m/min or specify
Power Source	220VAC 50/60HZ



SMA-2B050L

SMA-2B060L

Specification

Model	Size	Dimension (L x W x H) (mm)	Effective PCB Size (L x W) (mm)	Approximate Weight (Kg)
SMA-2A100L	L	1000 x 742 x 930	50x50-445x330	95
SMA-2A100XL	XL	1000x 840 x 930	50x50-530x460	110
SMA-2B050L	L	500 x 700 x 915	50x50-445x330	85
SMA-2B050XL	XL	500 x 840 x 915	50x50-445x460	90
SMA-2B060L	L	600 x 742 x 915	50x50-445x330	90
SMA-2B060XL	XL	600 x 840 x 915	50x50-445x460	95
SMA-2B070L	L	700 x 707 x 915	50x50-445x330	90